



DESIGN FEATURES

When the project requires a strong and durable wrap, ProSelect™ is the choice for the professional builder. Whether the job specification is for a base line wrap, or to be the primary wrap in a stucco or stone application where the wrap provides the primary drain plane, or any other traditional housewrap use, then PROSELECT™ is an ideal choice.

Manufactured in an identical process as our TWD but without the drainage plane creating filaments, PROSELECT™ is a heavy duty product that will endure the tests of time and wind to provide the needed moisture management on the wall. With a perm rating of 19, the drying of the structure from inevitable moisture intrusion will be first rate and efficient with PROSELECT™.

In a convenient and easily handled 5 foot by 200 foot roll weighing only 25 pounds, PROSELECT™ is easy to use at any level of the wall. No more trying to fight the wind as the oversized roll becomes a sail. PROSELECT™ is unique in its development for focusing on improving the building quality as well as the installation quality.

VAPOR PERMEABLE (perm rating of 19)

This innovative product effectively eliminates excess moisture and mitigates the damaging effects of mold and rot.

MEET ALL EXISTING CODE REQUIREMENTS

Choosing the right housewrap requires an understanding of the product's key attributes, including Water Resistance, Durability and Vapor Permeability.

BEST PRACTICE INSTALLATION

The biggest key with the installation of ProSelect™ Commercial Wrap and Tamlyn XtremeFlashing™ is to always install in **SHINGLE FASHION** so installation will begin at the base of the wall and openings and move vertically. Seam overlap will be 6" on all verticals and horizontals and 12" at corners. Preferred method for the flashing of openings in the Modified I but most important is to properly install Tamlyn XtremeFlashing™ shingle fashion.

SPECIFICATION

ITEM ID	TWC5X200
WIDTH	5 ft
LENGTH	200 ft
COVERAGE	1000 sf
ROLL WEIGHT	25 lbs
VAPOR PERMEANCE	19 perms
THICKNESS	0.3 mm
UV RATING	Maximum 120 days
WARRANTY	15 or 25-year limited
FIRE RATING	Class A

