

DESIGN FEATURES



DRAINS 2X FASTER THAN OTHER DRAINABLE WRAPS

This is achieved through the gap created by 1.5 mm spacers bonded to a high performance housewrap. This patented gap design provides a true drainage space between the sheathing and cladding material.

HAS DRYING CAPABILITY OF A 3/8 RAINSCREEN

There is growing recognition among building scientists and building codes that walls also need to drain, and, going forward, housewraps will increasingly be judged by how effectively they provide positive drainage of water from the wall.

CAN BE INSTALLED IN ANY DIRECTION

Housewraps, especially drainable wraps with enhanced drainage capabilities engineered into them, are increasingly being viewed as essential components of any well-constructed building. TamlynWrap® is a more cost effective product because it can be installed at any position, horizontally, vertically or diagonally.

VAPOR PERMEABLE (perm rating of 19)

This innovative product effectively eliminates excess moisture and mitigates the damaging effects of mold and rot.

MEETS ALL EXISTING CODE REQUIREMENTS FOR DRAINABILITY

Choosing the right housewrap requires an understanding of the product's key attributes, including Water Resistance, Durability, Vapor Permeability and Drainage.

BEST PRACTICE INSTALLATION

The biggest key with the installation of TamlynWrap® and Tamlyn XtremeFlashing™ is to always install in **SHINGLE FASHION** so installation will begin at the base of the wall and openings and move vertically. Seam overlap will be 6" on all verticals and horizontals and 12" at corners. Preferred method for the flashing of openings in the Modified I but most important is to properly install Tamlyn XtremeFlashing™ shingle fashion.

SPECIFICATION

ITEM ID	TWD5X100
WIDTH	5 ft
LENGTH	100 ft
COVERAGE	500 sf
ROLL WEIGHT	17 lbs
VAPOR PERMEANCE	19 perms
THICKNESS	1.8 mm
DRAINAGE GAP	1.5 mm
UV RATING	Maximum 120 days
WARRANTY	15 or 25-year limited
FIRE RATING	Class A

The New Standard with a Wrap and Gap all in one

