

TWC - TamlynWrap® ProSelect™ Commercial Wrap

Tech Support / Sales: 800-334-1676
www.tamlyn.com

DESIGN FEATURES

When the project requires a strong and durable wrap, **ProSelect™** is the choice for the professional builder. ProSelect™ is a high performance water and air resistive barrier product designed for the harsh conditions of a jobsite. ProSelect™ is made from multiple non-woven and barrier layers that provide superior durability, moisture and air infiltration protection.

In a convenient and easily handled 5 foot by 200 foot roll weighing only 25 pounds, ProSelect™ is easy to use at any level of the wall. This roll size facilitates the installation process at elevated heights and improves safety associated with wind events. ProSelect™ is unique in its development for focusing on improving building performance as well as the installation quality and safety.

VAPOR PERMEABLE (perm rating of 19)

The vapor permeability facilitates drying of wall components and mitigates potential moisture accumulation as well as the damaging effects of mold and rot.

MEETS ALL EXISTING CODE REQUIREMENTS

Meets or exceeds the ICC acceptance criteria requirements for water resistive barriers (AC38).

BEST PRACTICE

ProSelect™ must be installed **SHINGLE FASHION** and integrated with other wall components to promote positive mechanical drainage. All horizontal and vertical overlaps shall be 6" with 12" vertical overlap at any corners. Cap fasteners must be used for attachment per installation guidelines.



ITEM ID	TWC5X200
WIDTH	5 ft
LENGTH	200 ft
COVERAGE	1000 sf
ROLL WEIGHT	25 lbs
VAPOR PERMEANCE	19 perms
THICKNESS	0.3 mm
UV RATING	Maximum 270 days
WARRANTY	15-25 year limited
FIRE RATING	Class A