


WF



DESIGN FEATURES

Galvanized Window Flashing provides an inexpensive and easy to install method of stopping water penetration behind siding. Horizontal shelf is sloped 5-7 degrees toward outside wall.

MATERIAL

Available in Bldr, or STD, or 26 Ga GZD or standard colors as listed.

*For PAINTED specify stock color -AM- Almond, BR -Brown, BK -Black, CB - Charcoal, WH - White, Other colors are Special order.

ITEM ID	A	B	C
WF34126	6"	1/2"	3/4"
WF346	6"	3/4"	1/2"
WF834	8"	3/4"	1/2"
WF100	1-5/8"	1"	3/8"
WF112	1-1/2"	1-1/8"	3/8"
WF114	1-1/2"	1-1/4"	3/8"
WF10	2-1/4"	1-1/4"	1/2"
WF411412	4"	1-1/4"	1/2"
WF106	1-1/2"	1-1/2"	1/2"
WF102	2-1/8"	1-1/2"	3/8"
WF103	2"	1-1/2"	1/2"
WF211238	2"	1-1/2"	3/8"
WF121123	3"	1-1/2"	1/2"
WF126	6"	1-1/2"	1/2"
WF12134	1-3/4"	1-3/4"	1/2"
WF122112	1-1/2"	2"	1/2"
WF134	1-3/4"	2"	1/4"
WF212	2"	2-1/2"	1/2"
WF12212212	2-1/2"	2-1/2"	1/2"
WF122124	4"	2-1/2"	1/2"
WF122126	6"	2-1/2"	1/2"
WF1233	3"	3"	1/2"
WF3126	6"	3-1/2"	1/2"
WF2312	2-1/2"	3-1/2"	1/2"
WF12334334	3-3/4"	3-3/4"	1/2"
WF412712	4-1/2"	7"	1/2"

ITEM ID	A	B	C
WF100-105	1-5/8"	1"	3/8"
WF103-105	2"	1-1/2"	1/2"
WF12334334-108	3-3/4"	3-3/4"	1/2"
WF3126-110	6"	3-1/2"	1/2"
WF344147-108	7"	4-1/4"	3/4"
WF51251212-135	5-1/2"	5-1/4"	1/2"

