

TWD

DESIGN FEATURES

TamlynWrap® Drainable WRB is a unique moisture management product from Tamlyn. This innovative product combines a high performance Water Resistant Barrier (WRB) with a unique drainage pattern. Its unique design can remove 100 times more bulk water from a wall versus standard wraps.

DRAINS FASTER THAN OTHER DRAINABLE WRAPS

This is achieved through the gap created by 1.5 mm non-compressible spacers bonded to a high performance Water Resistance Barrier (WRB). This patented design provides a physical drainage space between the sheathing and cladding material.

CAN BE INSTALLED IN ANY DIRECTION

This patented technology is omni-directional which offers installation flexibility vs other options on the market.

VAPOR PERMEABLE (perm rating of 19)

The vapor permeability facilitates drying of wall components and mitigates potential moisture accumulation as well as the damaging effects of mold and rot.


MEETS ALL EXISTING CODE REQUIREMENTS FOR DRAINABILITY

Meets or exceeds the ICC acceptance criteria requirements for water resistive barriers (AC308) and drainage efficiency.

BEST PRACTICE

TamlynWrap® Drainable Wrap must be installed SHINGLE FASHION and integrated with other wall components to promote positive mechanical drainage. All horizontal and vertical overlaps shall be 6" with 12" vertical overlap at any corners. All vertical seams shall be taped and cap fasteners used for attachment per installation guidelines.

ITEM ID	TWD5X100
WIDTH	5 ft
LENGTH	100 ft
COVERAGE	500 sf
ROLL WEIGHT	17 lbs
VAPOR PERMEANCE	19 perms
THICKNESS	1.8 mm
DRAINAGE GAP	1.5 mm
UV RATING	Maximum 180 days
WARRANTY	15-25 year limited
FIRE RATING	Class A



Sheathing

TamlynWrap® Drainable 1.5

1.5 mm Non-Compressible Spacers

