

DESIGN FEATURES

XtremeSealant™ is a paintable, fast-curing sealant formulated to exhibit superior adhesion and flexibility to a wide variety of substrates including: PVC, aluminum, glass, stainless steel, galvanized steel, wood, FRP, marble, stone and laminate substrates. XtremeSealant™ is a solvent-free, non-isocyanate adhesive/sealant. Conforms to ASTM C920, Type S, Grade NS, Class 25. AAMA 808.3 Specification for Exterior Perimeter Sealing Compound.

STORAGE LIFE

12 months, unopened containers in conditioned space.

PAINTABLE

Testing prior to painting is recommended.

PACKAGING

XtremeSealant™ is available in 300 ml (10.1 fl oz) tube and 24 tubes per carton.



UTILITY MOISTURE FLASH

UMF

DESIGN FEATURES

Utility Moisture Flash is a heavy duty, flexible, tear-resistant, woven polypropylene nail-on flashing. Utility Moisture Flash was engineered to provide excellent durability when exposed to high ultraviolet rays and has the ability to withstand high winds. The cross woven design is to be mechanically fastened with capped fasteners. Easy to integrate with a water-resistant barrier, flashing and other wall components.

PACKAGING

12" Width x 120' Length, 20 rolls per box.

