

XtremeFlashing™ Tape
BUTYL

Tech Support / Sales: 800-334-1676
www.tamlyn.com



FEATURES / BENEFITS

- 20 mil uniform thickness
- Self-seals around fasteners
- Adheres to most building materials
- No adhesive staining or bleeding
- Can be installed with temperatures as low as 10°F
- Primer recommended for challenging conditions
- Improves energy efficiency
- 12 month shelf life in conditioned space
- 15 year limited warranty
- Available in 4", 6", 9" and 12" wide rolls
- Complies with ICC and AAMA 711 requirements



WSB (BUTYL ADHESIVE)

ITEM ID	WIDTH	LENGTH	THICKNESS
WSB20-4	4"	75'	20 mil
WSB20-6	6"	75'	20 mil
WSB20-9	9"	75'	20 mil
WSB20-12	12"	75'	20 mil

XtremeFlashing™ is a self-adhering, self-sealing flashing tape designed for use around windows, doors, building seams and in general construction. It is composed of a polymer film that is coated with an aggressive Broad Temperature Spectrum (BTS) butyl adhesive. This advanced butyl adhesive is suitable for extreme temperature applications. A release liner protects the adhesive and is removed as the tape is installed. The BTS adhesive self-seals around punctures such as nails and staples. This advanced system bonds to all common building and window materials and seals around fasteners.

Provides a water tight seal that integrates with other wall components for water management around windows, doors and other wall penetrations such as pipes, electrical conduit, through wall flashing and other flashing details. Must be installed SHINGLE FASHION for proper moisture management.