

Water Management System
TAMLYN[®] XtremeDeckTape

Tech Support / Sales: 800-334-1676
www.tamlyn.com



Private Label & Packaging Available

DESIGN FEATURES

Tamlyn[®] XtremeDeckTape is a self-adhering, self-sealing waterproofing tape designed for on top of decks, joists, and beams. Creates a protective seal around screws to prevent water penetration. It is composed of a polymer film that is coated with an aggressive Broad Temperature Spectrum (BTS[™]) butyl adhesive. This advanced butyl adhesive is suitable for extreme temperature applications. A release liner protects the adhesive and is removed as the tape is installed. The BTS[™] adhesive self-seals around punctures caused by nails and staples. This advanced system bonds to all common building materials and seals around fasteners.

DESIGN FEATURES

- Self-seals around fasteners including nails, staples and screws.
- UV-resistant black tape that blends between deck boards.
- Protects against water, air, insect and noise infiltration.
- Compatible with most common building materials.
- Butyl adhesive won't crack, dry, run or stain.
- Integrates with other wall components.
- Uniform thickness.
- Available in 3" wide rolls.

WARRANTY

15 Years Limited Warranty, contact Tamlyn for warranty details and limitations or visit www.tamlyn.com

TECHNICAL SPECIFICATION

PROPERTY	TEST METHOD	*TEST RESULT
Material Thickness	ASTM D 3767	20 Mils Nom.
Pliability	AAMA 711	Pass
Vaper Permeance	ASTM E 96	0.008 MAX
Nail Sealability	AAMA 711	Pass
Breaking Strength	AAMA 711	Pass
Elongation	AAMA 711	>500%
Material Classification	AAMA 711	Class A (no primer) Level 3 thermal exposure (80C/176F)
Application Temperature		>10F
UV Exposure Limit		120 Days

Complies with: AAMA 711-22

*Based on testing averages

